

CONVENIENT • EFFICIENT • ECO-FRIENDLY

# PureFlo® Brio Premier

POU Water Cooler



The semi-touchless PureFlo® Brio point-of-use (POU) water cooler is a convenient, efficient way to provide hot and cold purified drinking water in your home or business. This freestanding unit incorporates advanced carbon shaker filtration technology to ensure your family, employees and guests enjoy an endless supply of pure, delicious water at the touch of a button.

## Carbon filtration benefits

- Removes chlorine, chloramine, chemicals, pharmaceuticals, taste and odor
- Leaves minerals in the water
- Filtration components certified by the Water Quality Association (WQA) to meet standards: NSF/ANSI 42, 401,372 & CSA B483.1

## Carbon Shaker™ filtration technology

- High-quality filter media attached to the cooler compressor
- Compressor vibrates the filter and media multiple times per hour, creating new pathways for water
- Extends filter quality, longevity and effectiveness over traditional carbon filters
- Longer filter life helps lessen environmental impact

## Valuable everyday benefits

- Dispenser connects to the existing water supply to ensure water is always on hand and eliminate the need to store bottles
- Child safety lock on the hot water spout to help prevent accidents
- 100% stainless-steel cold and hot reservoirs for water purity and cooler longevity

## Convenient professional installation

- Hard-plumbed
- Does not require a drain connection

## Sleek design

- Fingerprint-resistant finish
- Easy to clean
- Compact design fits most spaces

**PUREFLO®**

CONVENIENT • EFFICIENT • ECO-FRIENDLY

# PureFlo® Brio Premier

POU Water Cooler



## Technical Specifications

Product Height: 44"

Product Width: 11"

Product Depth: 18"

Product Weight: 48 lbs.

Power Rating: 110-115V; 60Hz

Consumption Power: 350W heating; 100W cooling

Cold Water Temperature Range: 4°C – 10°C, 39.2°F – 50°F

Cold Water Continuous Discharging Capacity:  
About 1.6L/.42 gal

Cold Water Tank Capacity: About 3.2 L/108.8 oz./.85 gal  
(stainless-steel tank)

Hot Water Temperature Range: 80°C – 90°C, 176°F – 194°F

Hot Water Continuous Discharging Capacity: About  
1.6L/.42 gal

Hot Water Tank Capacity: About 2 L/67.84 oz./.53 gal  
(stainless-steel tank)

Recommended Number of Users: 1-40\*

\*Data is based on recommended eight 8-ounce glasses a day

**PUREFLO®**

